



Hardware Specifications

Conductor 500 Series

PHYSICAL AND POWER SPECIFICATIONS

Ethernet Ports	8 x GbE RJ-45 ports 10/100/1000M, for use with STP or UTP cables. 2 x SFP 1000 BASE-X
Ethernet Expansion Bays	1
Power Supply (dual)	100-240 Vac 47-63 Hz
Power Consumption	270W, max
Controls	1 Reboot button (actuated with pin) 1 Reset button (actuated with pin) 4 Push-buttons for LCD display unit 1 Power supply alert mute (back of unit)
Displays	1 Power LED 1 Activity LED 1 Status LED 1 Alert LED 1 2-line x 20-character LCD configuration and management front panel
Storage Temp Range	-20° to 70° C (-4° to 158° F)
Operating Temp Range	Primary power: 0°C to +45°C (+32°F to +113°F) Secondary power: 0°C to +40°C (+32°F to 104°F)
Operating Humidity	5% to 90%, non-condensing
Mounting	1U Rack-mount
Dimensions	450mm W x 430mm D x 44mm H (17.7" W x 16.93" D x 1.74" H)
Weight	8.5 kg (18.74 lb)

REGULATORY APPROVALS

EMC	FCC Part 15 B Class A (USA) ICES-0003 Issue 6-2016 Class A (Canada) ANSI C63.4-2014 EN 55032 / CISPR 32 EN 55024 / CISPR 24 AS/NZS CISPR 32 VCCI-CISPR 32
Safety	IEC 60950-1 UL 60950-1 2nd Edition CAN/CSA C22.2 NO. 60950-1-07 2nd Edition EN 60950-1:2006+A11:2009+A1:2010+A12:2011+A2:2013
Compliance Marks	c(UL)us (USA/Canada) FCC RCM (Australia / NZ) VCCI (Japan) CE